

LIQUID TIGHT FLEXIBLE STEEL CONDUIT

Material	HDG Steel + PVC compound
Properties	Helically wound. Square lock flexible conduit with heavy smooth PVC cover coating, strong square lock. IP Rating: IP65. Colors: Available in Grey. Temperature: -20 C to +70 C
Features	• PVC Cover will have minimal wrinkle when bent. • Oil and grease resistant. • UV resistant and suitable for external use.
Applications	• Indoor and Outdoor installations where liquid tight proofing is required • Cable management for conveyors, blowers, crane hoist, HVAC machine and equipments etc... • Concealed or exposed installations • Designed for both commercial and industrial applications.



Item Code	Trade Size	Internal Diameter (mm)		Outside Diameter (mm)		Min. Bend Radius (mm)	Coil Packing (M)
		Min	Max	Min	Max		
C-ASLTFCM050	1/2"	15.8	16.31	20.83	20.1	85	30
C-ASLTFM075	3/4"	20.83	21.34	26.16	25.2	100	30
C-ASLTFM100	1"	26.44	27.08	32.77	32.1	120	30
C-ASLTFM125	1 1/4"	35.05	35.81	41.40	42.16	150	15
C-ASLTFM150	1 1/2"	40.00	40.64	47.37	48.26	180	15
C-ASLTFM200	2"	51.50	51.94	59.44	60.33	220	15

***Other sizes can be supplied upon request